



according to UK REACH Regulation

Nital 5% (aq)

Revision date: 28.03.2022 Product code: Page 1 of 12

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Nital 5% (aq)

UFI: MK00-6XGE-FSJS-P7D0

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Laboratory chemical

Uses advised against

Any non-intended use.

1.3. Details of the supplier of the safety data sheet

Company name: Schmitz-Metallographie GmbH

Street: Kaiserstraße 100
Place: D-52134 Herzogenrath

Telephone: 02407 / 568296-0 Telefax: 02407 / 568296-9

e-mail: info@schmitz-metallographie.de

Contact person: Herr Füllmann

e-mail: info@schmitz-metallographie.de Internet: www.schmitz-metallographie.de

Responsible Department: Dr. Gans-Eichler e-mail: info@tge-consult.de Chemieberatung GmbH e-mail: info@tge-consult.de Tel.: +49(0)2534 6441185

Otto-Hahn-Str. 36 www.tge-consult.de

D-48161 Münster

1.4. Emergency telephone

Poison Information Center Mainz, Germany, Tel: +49(0)6131/19240

<u>number:</u>

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

GB CLP Regulation

Met. Corr. 1; H290 Skin Irrit. 2; H315 Eye Dam. 1; H318

Full text of hazard statements: see SECTION 16.

2.2. Label elements

GB CLP Regulation

Hazard components for labelling

nitric acid ... %

Signal word: Danger

Pictograms:



Hazard statements

H290 May be corrosive to metals.
H315 Causes skin irritation.
H318 Causes serious eye damage.



according to UK REACH Regulation

Nital 5% (aq)

Revision date: 28.03.2022 Product code: Page 2 of 12

Precautionary statements

P234 Keep only in original packaging.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P302+P352 IF ON SKIN: Wash with plenty of water.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P332+P313 If skin irritation occurs: Get medical advice/attention.
P390 Absorb spillage to prevent material damage.

Special labelling of certain mixtures

EUH071 Corrosive to the respiratory tract.

2.3. Other hazards

For information or further instructions, see also section 11 or 12.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Chemical characterization

in aqueous solution

Hazardous components

CAS No	Chemical name			Quantity		
	EC No	EC No Index No REACH No				
	Classification (GB CLP Regulation	Classification (GB CLP Regulation)				
7697-37-2	nitric acid %	nitric acid %				
	231-714-2	007-030-00-3	01-2119487297-23			
	Ox. Liq. 3, Acute Tox. 3, Skin Corr. 1A; H272 H331 H314 EUH071					

Full text of H and EUH statements: see section 16.

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
	Specific Conc. I	Limits, M-factors and ATE	
7697-37-2	231-714-2	nitric acid %	3 - < 5 %
	inhalation: ATE 2,65 mg/kg (vapours); inhalation: LC50 = 2500 ppm (gases) Ox. Liq. 3; H272: >= 65 - 100 Skin Corr. 1A; H314: >= 20 - 100 Skin Corr. 1B; H314: >= 5 - < 20		

Further Information

Product does not contain listed SVHC substances > 0,1 % according to Regulation (EC) No. 1907/2006 Article 59 (REACH)

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible). Take off immediately all contaminated clothing.

After inhalation

In case of accident by inhalation: remove casualty to fresh air and keep at rest. In case of respiratory tract irritation, consult a physician.

After contact with skin

Gently wash with plenty of soap and water. In case of skin irritation, seek medical treatment.

After contact with eves

Rinse cautiously with water for several minutes. In case of troubles or persistent symptoms, consult an ophthalmologist.





according to UK REACH Regulation

Nital 5% (aq)

Revision date: 28.03.2022 Product code: Page 3 of 12

After ingestion

Rinse mouth thoroughly with water. Let water be drunken in little sips (dilution effect). Do NOT induce vomiting. In all cases of doubt, or when symptoms persist, seek medical advice.

4.2. Most important symptoms and effects, both acute and delayed

No information available.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

The product itself does not burn.

Unsuitable extinguishing media

High power water jet.

5.2. Special hazards arising from the substance or mixture

Can be released in case of fire: Nitrogen oxides (NOx).

5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus. In case of fire and/or explosion do not breathe fumes.

Additional information

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

Co-ordinate fire-fighting measures to the fire surroundings.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General advice

Safe handling: see section 7

For non-emergency personnel

Wear personal protection equipment (refer to section 8).

For emergency responders

No special measures are necessary.

6.2. Environmental precautions

Do not allow to enter into surface water or drains. Discharge into the environment must be avoided.

6.3. Methods and material for containment and cleaning up

For containment

Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents).

Treat the recovered material as prescribed in the section on waste disposal.

For cleaning up

Clean contaminated objects and areas thoroughly observing environmental regulations.

Other information

Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents).

Treat the recovered material as prescribed in the section on waste disposal.

Clean contaminated objects and areas thoroughly observing environmental regulations.

6.4. Reference to other sections

Disposal: see section 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling



according to UK REACH Regulation

Nital 5% (aq)

Revision date: 28.03.2022 Product code: Page 4 of 12

Advice on safe handling

Wear suitable protective clothing. See section 8.

Advice on protection against fire and explosion

Usual measures for fire prevention.

Advice on general occupational hygiene

Always close containers tightly after the removal of product. Do not eat, drink, smoke or sneeze at the workplace. Wash hands before breaks and after work.

Further information on handling

General protection and hygiene measures: See section 8.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed in a cool, well-ventilated place.

Hints on joint storage

Do not store together with: Explosives. Oxidizing solids. Oxidizing liquids. Radioactive substances. Infectious substances. Food and animal feedingstuff.

Further information on storage conditions

Keep the packing dry and well sealed to prevent contamination and absorbtion of humidity.

Recommended storage temperature: 20°C

Protect against: frost. UV-radiation/sunlight. heat. Humidity

7.3. Specific end use(s)

See section 1.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure limits (EH40)

CAS No	Substance	ppm	mg/m³	fibres/ml	Category	Origin
7697-37-2	Nitric acid	1	2.6		STEL (15 min)	WEL

DNEL/DMEL values

CAS No	Substance				
DNEL type		Exposure route	Effect	Value	
7697-37-2	nitric acid %				
Worker DNEL,	long-term	inhalation	local	2,6 mg/m³	
Consumer DNEL, long-term		inhalation	local	1,3 mg/m³	
Consumer DNEL, acute		inhalation	local	1,3 mg/m³	

8.2. Exposure controls







Appropriate engineering controls

Technical measures and the application of suitable work processes have priority over personal protection equipment.

Provide adequate ventilation.

Individual protection measures, such as personal protective equipment



according to UK REACH Regulation

Nital 5% (aq)

Revision date: 28.03.2022 Product code: Page 5 of 12

Eye/face protection

Wear safety glasses; chemical goggles (if splashing is possible). BS/EN 166

Hand protection

Wear suitable gloves.

Suitable material:

FKM (fluororubber). - Thickness of glove material: 0,4 mm

Breakthrough time >= 8 h

Butyl rubber. - Thickness of glove material: 0,5 mm

Breakthrough time >= 8 h

CR (polychloroprenes, Chloroprene rubber). - Thickness of glove material: 0,5 mm

Breakthrough time >= 8 h

NBR (Nitrile rubber). - Thickness of glove material: 0,35 mm

Breakthrough time >= 8 h

PVC (Polyvinyl chloride). - Thickness of glove material: 0,5 mm

Breakthrough time >= 8 h

For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

The selected protective gloves have to satisfy the specifications of EU Directive EC/2016/425 and the standard EN ISO 374 derived from it.

Check leak tightness/impermeability prior to use. In the case of wanting to use the gloves again, clean them before taking off and air them well.

Skin protection

Suitable protective clothing: Lab apron.

Minimum standard for preventive measures while handling with working materials are specified in the TRGS 500 (D).

Respiratory protection

With correct and proper use, and under normal conditions, breathing protection is not required.

Respiratory protection necessary at:

- -Exceeding exposure limit values
- -Insufficient ventilation and aerosol or mist formation

Suitable respiratory protective equipment: particulates filter device (DIN EN 143). Type: P1-3

The filter class must be suitable for the maximum contaminant concentration (gas/vapour/aerosol/particulates) that may arise when handling the product. If the concentration is exceeded, self-contained breathing apparatus must be used.

Environmental exposure controls

Do not allow uncontrolled discharge of product into the environment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state: liquid
Colour: colourless
Odour: characteristic

Changes in the physical state

Melting point/freezing point:

Boiling point or initial boiling point and

not determined

boiling range:

Sublimation point:

Softening point:

Pour point:

Plash point:

not determined
not determined
not determined
not determined
not determined



according to UK REACH Regulation

Nital 5% (aq) Product code: Page 6 of 12

Explosive properties

Revision date: 28.03.2022

none

Lower explosion limits:

Upper explosion limits:

not determined

not determined

not determined

not determined

Self-ignition temperature

Gas: not determined
Decomposition temperature: not determined
pH-Value: 0
Viscosity / dynamic: not determined
Viscosity / kinematic: not determined
Flow time: not determined
Water solubility: completely miscible
(at 20 °C)

Solubility in other solvents

not determined

Partition coefficient n-octanol/water:

Vapour pressure:

Vapour pressure:

Not determined

Density:

Relative vapour density:

SECTION 12: Ecological information

not determined

not determined

not determined

not determined

9.2. Other information

Information with regard to physical hazard classes

Sustaining combustion: Not sustaining combustion

Oxidizing properties

none

Other safety characteristics

Solvent separation test:

Solvent content:

not determined

Solid content:

not determined

rate:

not determined

not determined

Further Information

SECTION 10: Stability and reactivity

10.1. Reactivity

May be corrosive to metals.

10.2. Chemical stability

The product is chemically stable under recommended conditions of storage, use and temperature.

10.3. Possibility of hazardous reactions

Violent reaction with: Base.

Reacts with: Substances which form flammable gases when in contact with water. Organic peroxides.

Inflammatory substances. Alkali metals. Oxidizing agents.

10.4. Conditions to avoid

In case of warming: Ignition hazard.

Keep away from heat.



according to UK REACH Regulation

Nital 5% (aq)

Revision date: 28.03.2022 Product code: Page 7 of 12

Keep away from sources of ignition. - No smoking.

10.5. Incompatible materials

Materials to avoid: Hazardous substances that release flammable gases when in contact with water. Organic peroxides. Alkali metals. Oxidizing agents.

10.6. Hazardous decomposition products

Can be released in case of fire: Nitrogen oxides (NOx).

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in GB CLP Regulation

Toxicocinetics, metabolism and distribution

No information available.

Acute toxicity

Based on available data, the classification criteria are not met.

CAS No	Chemical name					
	Exposure route	Dose	Species	Source	Method	
7697-37-2	nitric acid %					
	inhalation vapour	ATE 2,65 mg/kg				
	inhalation (4 h) gas	LC50 2500 ppm	Rat	ECHA Dossier		

Irritation and corrosivity

Causes skin irritation.

Causes serious eye damage.

Sensitising effects

Based on available data, the classification criteria are not met.

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

Specific effects in experiment on an animal

No data available.

11.2. Information on other hazards

Endocrine disrupting properties

No data available.

SECTION 12: Ecological information

12.1. Toxicity

The product has not been tested.

The product has not been tested.							
CAS No	Chemical name						
	Aquatic toxicity	Dose		[h] [d]	Species	Source	Method
7697-37-2	nitric acid %						
	Acute crustacea toxicity	EC50	2.5 mg/l	48 h	Ceriodaphnia spec	ECHA Dossier	

12.2. Persistence and degradability



according to UK REACH Regulation

Nital 5% (aq)

Revision date: 28.03.2022 Product code: Page 8 of 12

The product has not been tested.

12.3. Bioaccumulative potential

No indication of bioaccumulation potential.

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
7697-37-2	nitric acid %	-0,21

12.4. Mobility in soil

No data available.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to UK REACH.

The aforementioned statement applies to substances contained in the product with a minimum content of 0.1 %

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

The aforementioned statement applies to substances contained in the product with a minimum content of 0.1 %

12.7. Other adverse effects

No data available.

Further information

Do not allow to enter into surface water or drains.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Observe in addition any national regulations! Consult the local waste disposal expert about waste disposal. Non-contaminated packages may be recycled.

According to (EWC) European Waste Catalogue, allocation of waste identity numbers/waste descriptions must be carried out in a specific way for every industry and process.

Control report for waste code/ waste marking according to (EWC) European Waste Catalogue:

List of Wastes Code - residues/unused products

110105

WASTES FROM CHEMICAL SURFACE TREATMENT AND COATING OF METALS AND OTHER MATERIALS; NON-FERROUS HYDRO-METALLURGY; wastes from chemical surface treatment and coating of metals and other materials (for example galvanic processes, zinc coating processes, pickling processes, etching, phosphating, alkaline degreasing, anodising); pickling acids; hazardous waste

List of Wastes Code - used product

110105

WASTES FROM CHEMICAL SURFACE TREATMENT AND COATING OF METALS AND OTHER MATERIALS; NON-FERROUS HYDRO-METALLURGY; wastes from chemical surface treatment and coating of metals and other materials (for example galvanic processes, zinc coating processes, pickling processes, etching, phosphating, alkaline degreasing, anodising); pickling acids; hazardous waste

List of Wastes Code - contaminated packaging

150110

WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately collected municipal packaging waste); packaging containing residues of or contaminated by hazardous substances; hazardous waste

Contaminated packaging

Handle contaminated packages in the same way as the substance itself.



according to UK REACH Regulation

Nital 5% (aq)

Revision date: 28.03.2022 Product code: Page 9 of 12

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number or ID number: UN 3264

14.2. UN proper shipping name: CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S. (Nitric acid)

14.3. Transport hazard class(es):814.4. Packing group:IIIHazard label:8



Classification code: C1
Special Provisions: 274
Limited quantity: 5 L
Excepted quantity: E1
Transport category: 3
Hazard No: 80
Tunnel restriction code: E

Inland waterways transport (ADN)

14.1. UN number or ID number: UN 3264

14.2. UN proper shipping name: CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S. (Nitric acid)

14.3. Transport hazard class(es):814.4. Packing group:IIIHazard label:8



Classification code: C1
Special Provisions: 274
Limited quantity: 5 L
Excepted quantity: E1

Marine transport (IMDG)

14.1. UN number or ID number: UN 3264

14.2. UN proper shipping name: CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S. (Nitric acid)

14.3. Transport hazard class(es):814.4. Packing group:IIIHazard label:8



Marine pollutant:

Special Provisions:

Limited quantity:

Excepted quantity:

EmS:

F-A, S-B

Segregation group:

NO

223, 274

5 L

Et

E1

F-A, S-B

1 - acids

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number or ID number: UN 3264

14.2. UN proper shipping name: CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S. (Nitric acid)

14.3. Transport hazard class(es): 8
14.4. Packing group: | | | |



according to UK REACH Regulation

Nital 5% (aq)

Revision date: 28.03.2022 Product code: Page 10 of 12

Hazard label:



Special Provisions:

Limited quantity Passenger:

Passenger LQ:

Excepted quantity:

A3 A8

1 L

Y841

Excepted quantity:

E1

IATA-packing instructions - Passenger:852IATA-max. quantity - Passenger:5 LIATA-packing instructions - Cargo:856IATA-max. quantity - Cargo:60 L

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

14.6. Special precautions for user

Refer to section 6-8

14.7. Maritime transport in bulk according to IMO instruments

not relevant

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

Restrictions on use (REACH, annex XVII):

Entry 3

2010/75/EU (VOC):

No information available.

No information available.

Information according to 2012/18/EU Not subject to 2012/18/EU (SEVESO III)

(SEVESO III):

Additional information

Safety Data Sheet according to UK-REACH Regulation

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].

UK REACH Appendix XVII, No (mixture): 3

National regulatory information

Employment restrictions: Observe restrictions to employment for juveniles according to the 'juvenile

work protection guideline' (94/33/EC).

Water hazard class (D): 1 - slightly hazardous to water

15.2. Chemical safety assessment

For the following substances of this mixture a chemical safety assessment has been carried out:

nitric acid ... %

SECTION 16: Other information

Changes

Rev. 1,00; Initial release 28.03.2022

Abbreviations and acronyms

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

CAS: Chemical Abstracts Service

CLP: Classification, Labelling and Packaging of substances and mixtures



according to UK REACH Regulation

Nital 5% (aq)

Revision date: 28.03.2022 Product code: Page 11 of 12

DNEL: Derived No Effect Level

d: day(s)

EINECS: European INventory of Existing Commercial chemical Substances

ELINCS: European LIst of Notified Chemical Substances

ECHA: European Chemicals Agency EWC: European Waste Catalogue

IARC: INTERNATIONAL AGENCY FOR RESEARCH ON CANCER

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)

ICAO: International Civil Aviation Organization

ICAO-TI: Technical Instructions by the "International Civil Aviation Organization" (ICAO)

GHS: Globally Harmonized System of Classification and Labelling of Chemicals GefStoffV: Gefahrstoffverordnung (Ordinance on Hazardous Substances, Germany)

h: hour

LOAEL: Lowest observed adverse effect level

LOAEC: Lowest observed adverse effect concentration

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

NOAEL: No observed adverse effect level

NOAEC: No observed adverse effect concentration

NLP: No-Longer Polymers N/A: not applicable

OECD: Organisation for Economic Co-operation and Development

PNEC: predicted no effect concentration PBT: Persistent bioaccumulative toxic

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de

fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

REACH: Registration, Evaluation, Authorisation of Chemicals

SVHC: substance of very high concern TRGS: Technische Regeln für Gefahrstoffe

UN: United Nations

VOC: Volatile Organic Compounds

Classification for mixtures and used evaluation method according to GB CLP Regulation

Classification	Classification procedure				
Met. Corr. 1; H290	On basis of test data				
Skin Irrit. 2; H315	Calculation method				
Eye Dam. 1; H318	Calculation method				

Relevant H and EUH statements (number and full text)

H272	May intensify fire; oxidiser.
H290	May be corrosive to metals.

H314 Causes severe skin burns and eye damage.

H315 Causes skin irritation.
H318 Causes serious eye damage.

H331 Toxic if inhaled.

EUH071 Corrosive to the respiratory tract.

Further Information

Classification according to GHS [UK CLP] - Classification procedure:

Health hazards: Calculation method. Environmental hazards: Calculation method.

Physical hazards: On basis of test data and / or calculated and / or estimated.

The above information describes exclusively the safety requirements of the product and is based on our





according to UK REACH Regulation

Nital 5% (aq)

Revision date: 28.03.2022 Product code: Page 12 of 12

present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)