

Telefax: 02407 / 568296-9



Safety Data Sheet

according to Regulation (EC) No 1907/2006

coolTec II (Lubrikant_Alkoholbasis)

Revision date: 06.06.2023 Product code: Page 1 of 12

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

coolTec II (Lubrikant Alkoholbasis)

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Lubricants and diluents, metallographic sample preparation.

Uses advised against

Any non-intended use.

1.3. Details of the supplier of the safety data sheet

Company name: Schmitz-Metallographie GmbH

Street: Kaiserstraße 100
Place: D-52134 Herzogenrath
Telephone: 02407 / 568296-0

E-mail: info@schmitz-metallographie.de

Contact person: Herr Füllmann

E-mail: info@schmitz-metallographie.de Internet: www.schmitz-metallographie.de

1.4. Emergency telephone 02407 / 568296-0 (Mo-Fr 9:00 - 16:00)

number:

Further Information

Safety Data Sheet according to Regulation (EC) No. 1907/2006 (amended by Regulation (EU) No 2020/878)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No 1272/2008

Flam. Liq. 2; H225

Full text of hazard statements: see SECTION 16.

2.2. Label elements

Regulation (EC) No 1272/2008

Signal word: Danger

Pictograms:



Hazard statements

H225 Highly flammable liquid and vapour.

Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P233 Keep container tightly closed.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with

water.

P403+P235 Store in a well-ventilated place. Keep cool.

P501 Dispose of contents/container to local/regional/national/international regulations.



according to Regulation (EC) No 1907/2006

coolTec II (Lubrikant_Alkoholbasis)

Revision date: 06.06.2023 Product code: Page 2 of 12

2.3. Other hazards

In use, may form flammable/explosive vapour-air mixture.

The substances in the mixture (> 0.1%) do not meet the PBT/vPvB criteria according to REACH, annex XIII. This product does not contain a substance (> 0,1%) that has endocrine disrupting properties with respect to humans as no components meets the criteria. This product does not contain a substance (> 0,1 %) that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Hazardous components

CAS No	Chemical name			Quantity		
	EC No	EC No Index No REACH No				
	Classification (Regulation (EC) No 1272/2008)					
64-17-5	ethanol; ethyl alcohol					
	200-578-6	603-002-00-5				
	Flam. Liq. 2; H225					

Full text of H and EUH statements: see section 16.

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
	Specific Conc. Limits, M-factors and ATE		
64-17-5	200-578-6 ethanol; ethyl alcohol		90 - < 99 %
	inhalation: LC50 = 124,7 mg/l (vapours); oral: LD50 = >5000 mg/kg		

Further Information

Product does not contain listed SVHC substances > 0.1 % according to Regulation (EC) No. 1907/2006 Article 59 (REACH)

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible). Take off immediately all contaminated clothing.

First aider: Pay attention to self-protection!

After inhalation

Remove person to fresh air and keep comfortable for breathing. In case of respiratory tract irritation, consult a physician.

After contact with skin

Take off immediately all contaminated clothing. Wash with plenty of water. In case of skin irritation, seek medical treatment.

After contact with eyes

Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

After inaestion

Rinse mouth thoroughly with water. Let water be drunken in little sips (dilution effect). Do NOT induce vomiting. Never give anything by mouth to an unconscious person or a person with cramps. In all cases of doubt, or when symptoms persist, seek medical advice.

4.2. Most important symptoms and effects, both acute and delayed

See sections 2 and 11

4.3. Indication of any immediate medical attention and special treatment needed





according to Regulation (EC) No 1907/2006

coolTec II (Lubrikant_Alkoholbasis)

Revision date: 06.06.2023 Product code: Page 3 of 12

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Carbon dioxide (CO2). Dry extinguishing powder. Alcohol resistant foam.

In case of major fire and large quantities: Atomized water.

Unsuitable extinguishing media

High power water jet.

5.2. Special hazards arising from the substance or mixture

Can be released in case of fire: Gases/vapours, irritant. Carbon monoxide (CO). Carbon dioxide (CO2). Sulphurous oxides (SOx) Nitrogen oxides (NOx).

5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus. In case of fire and/or explosion do not breathe fumes.

Additional information

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water. Use water spray jet to protect personnel and to cool endangered containers.

In case of major fire and large quantities: Evacuate area. Fight fire remotely due to the risk of explosion.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General advice

Do not breathe gas/vapour/aerosol. Avoid contact with skin, eyes and clothes.

For non-emergency personnel

Remove persons to safety. Remove all sources of ignition. Ventilate affected area.

Wear personal protection equipment (refer to section 8).

For emergency responders

No special measures are necessary.

6.2. Environmental precautions

Do not allow to enter into surface water or drains. Danger of explosion! Cover drains. Prevent spread over a wide area (e.g. by containment or oil barriers). In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

6.3. Methods and material for containment and cleaning up

For containment

Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents). Ventilate affected area.

Treat the recovered material as prescribed in the section on waste disposal.

For cleaning up

Clean contaminated objects and areas thoroughly observing environmental regulations.

6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Provide adequate ventilation as well as local exhaustion at critical locations.

Do not breathe gas/vapour/aerosol. Avoid contact with skin, eyes and clothes.



according to Regulation (EC) No 1907/2006

coolTec II (Lubrikant_Alkoholbasis)

Revision date: 06.06.2023 Product code: Page 4 of 12

Wear suitable protective clothing. (See section 8.)

Advice on protection against fire and explosion

Keep away from sources of ignition. - No smoking. Take precautionary measures against static discharges. Flammable vapours can accumulate in head space of closed systems. In use, may form flammable/explosive vapour-air mixture. Heating causes rise in pressure with risk of bursting.

Advice on general occupational hygiene

The usual precautions for handling chemicals should be considered.

Keep away from food, drink and animal feedingstuffs.

Always close containers tightly after the removal of product. When using do not eat, drink or smoke. Wash hands before breaks and after work. Protect skin by using skin protective cream. Take off contaminated clothing and wash it before reuse.

Further information on handling

General protection and hygiene measures: See section 8.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed in a cool, well-ventilated place. Protect against direct sunlight.

Ensure adequate ventilation of the storage area.

Make sure spills can be contained (e.g. sump pallets or kerbed areas).

Hints on joint storage

Do not store together with: Gas. Explosives. Flammable solids. Pyrophoric liquids and solids. Self-heating substances and mixtures. Substances and mixtures which, in contact with water, emit flammable gases. Oxidizing liquids. Oxidizing solids. ammonium nitrate. Self-reactive substances and mixtures. Organic peroxides. Non-combustible toxic substances. Radioactive substances. Infectious substances.

Further information on storage conditions

Keep the packing dry and well sealed to prevent contamination and absorbtion of humidity.

Protect against: UV-radiation/sunlight. heat. Humidity frost.

storage temperature: 15 - 25°C

7.3. Specific end use(s)

See section 1

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

CAS No	Substance	ppm	mg/m³	fib/cm³	Category	Origin
64-17-5	Ethanol	1000	-		STEL (15 min)	

8.2. Exposure controls



Appropriate engineering controls

Technical measures and the application of suitable work processes have priority over personal protection equipment.

Provide adequate ventilation as well as local exhaustion at critical locations.

Individual protection measures, such as personal protective equipment

Eye/face protection

Recommended eye protection brand: Tightly sealed safety glasses. (EN 166)



according to Regulation (EC) No 1907/2006

coolTec II (Lubrikant_Alkoholbasis)

Revision date: 06.06.2023 Product code: Page 5 of 12

Hand protection

In case of prolonged or frequently repeated skin contact: Wear suitable gloves.

Suitable material: Butyl rubber. Thickness of glove material: 0,5 mm

Breakthrough time >= 480 min. Penetration time (maximum wearing period): ~ 120 min. (estimated)

For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

The selected protective gloves have to satisfy the specifications of EU Directive EC/2016/425 and the standard EN 374 derived from it.

Before using check leak tightness / impermeability. In the case of wanting to use the gloves again, clean them before taking off and air them well.

Skin protection

Wear fire/flame resistant/retardant clothing.

Respiratory protection

With correct and proper use, and under normal conditions, breathing protection is not required.

Respiratory protection necessary at:

Exceeding exposure limit values

Insufficient ventilation

Suitable respiratory protective equipment: gas filtering equipment (EN 141). type: A

The filter class must be suitable for the maximum contaminant concentration (gas/vapour/aerosol/particulates) that may arise when handling the product. If the concentration is exceeded, self-contained breathing apparatus must be used. Observe the wear time limits according GefStoffV in combination with the rules for using respiratory protection apparatus (BGR 190).

Environmental exposure controls

Do not allow uncontrolled discharge of product into the environment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state: liquid

Colour: not determined
Odour: characteristic
Odour threshold: not determined

Melting point/freezing point:

Boiling point or initial boiling point and

78 (Ethanol) °C

boiling range:

not determined Flammability: Lower explosion limits: 3,5 (Ethanol) vol. % 15 (Ethanol) vol. % Upper explosion limits: Flash point: 12 (Ethanol) °C Auto-ignition temperature: 400 (Ethanol) °C Decomposition temperature: not determined pH-Value: not determined Viscosity / kinematic: not determined Water solubility: not determined

Solubility in other solvents

not determined

Dissolution rate: not relevant Partition coefficient n-octanol/water: SECTION 12: Ecological information Dispersion stability: not relevant Vapour pressure: not determined Density: 0,79 g/cm³ Bulk density: not determined



according to Regulation (EC) No 1907/2006

coolTec II (Lubrikant_Alkoholbasis)

Revision date: 06.06.2023 Product code: Page 6 of 12

Relative vapour density: not determined Particle characteristics: not relevant

9.2. Other information

Information with regard to physical hazard classes

Explosive properties

In use, may form flammable/explosive vapour-air mixture.

Self-ignition temperature

Gas: not determined

Oxidizing properties

none.

Other safety characteristics

Evaporation rate: not determined Solvent separation test: not determined Solvent content: 90% Solid content: not determined Sublimation point: not determined Softening point: not determined Pour point: not determined Viscosity / dynamic: 1,19 (Ethanol) mPa·s Flow time: not determined

Further Information

No information available.

SECTION 10: Stability and reactivity

10.1. Reactivity

No information available.

10.2. Chemical stability

The mixture is chemically stable under recommended conditions of storage, use and temperature.

10.3. Possibility of hazardous reactions

No hazardous reaction when handled and stored according to provisions.

Refer to chapter 10.5.

10.4. Conditions to avoid

Keep away from heat. Danger of explosion!

In use may form flammable/explosive vapour-air mixture.

Heating causes rise in pressure with risk of bursting.

10.5. Incompatible materials

Materials to avoid: Oxidizing agents, strong. Reducing agents, strong. Strong acid. strong alkalis.

10.6. Hazardous decomposition products

Can be released in case of fire: Gas/vapours, irritant. Carbon monoxide Carbon dioxide (CO2). Sulphurous oxides (SOx) Nitrogen oxides (NOx).

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Toxicocinetics, metabolism and distribution

No data available.

Acute toxicity

Based on available data, the classification criteria are not met.



according to Regulation (EC) No 1907/2006

coolTec II (Lubrikant_Alkoholbasis)

Revision date: 06.06.2023 Product code: Page 7 of 12

ATEmix calculated

ATE (oral) > 2000 mg/kg; ATE (dermal) > 2000 mg/kg; ATE (inhalation vapour) > 20 mg/l; ATE (inhalation dust/mist) > 5 mg/l

CAS No	Chemical name						
	Exposure route	Dose		Species	Source	Method	
64-17-5	ethanol; ethyl alcohol						
	oral	LD50 >: mg/kg	5000	Rat	ECHA Dossier		
	inhalation (4 h) vapour	LC50 12 mg/l	24,7	Rat	ECHA Dossier		

Irritation and corrosivity

Based on available data, the classification criteria are not met.

Sensitising effects

Based on available data, the classification criteria are not met.

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

Ethanol:

In-vitro mutagenicity: No experimental indications of mutagenicity in-vitro exist. Reproductive toxicity: Exposure time: 18 weeks Species: CD-1 Mouse. Method: OECD Guideline 416

Result: NOAEL = 20700 mg/kg/day Developmental toxicity/teratogenicity: Exposure time: 19d Species: Sprague-Dawley Rat. Method: OECD Guideline 414 Result: NOAEL = 16000 ppm (maternal toxicity) Result: NOAEL >= 20000 ppm (teratogenicity) Literature information: ECHA Dossier

ethanediol; ethylene glycol:

In-vitro mutagenicity: Method: OECD Guideline 471 (Bacterial Reverse Mutation Assay) 1997; Result: negative. Literature information: ECHA Dossier; Carcinogenicity:; Method: oral. Species: Mouse. Exposure duration: 2 years. Result: NOAEL = 1500 mg/kg; Literature information: ECHA Dossier; Developmental toxicity/teratogenicity: Method: -; Species: Mouse.; Exposure duration: 20 d. Result: NOAEC = 2500 mg/m3; Literature information: ECHA Dossier

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Ethanol:

Subchronic oral toxicity:

Exposure time: 90d; Species: Sprague-Dawley Rat.

Method: OECD Guideline 408; Result: NOAEL = 1280 mg/kg; Literature information: ECHA Dossier

ethanediol; ethylene glycol:

Subacute oral toxicity: Method: OECD Guideline 410 (Repeated Dose Dermal Toxicity: 21/28-Day Study); Species: Dog.; Exposure duration: 28 d. Results: NOAEL = 2200 mg/kg(bw)/day; Literature information: ECHA Dossier

Aspiration hazard

Based on available data, the classification criteria are not met.

Specific effects in experiment on an animal

No data available.

11.2. Information on other hazards

Endocrine disrupting properties

This product does not contain a substance (> 0,1%) that has endocrine disrupting properties with respect to humans as no components meets the criteria.



according to Regulation (EC) No 1907/2006

coolTec II (Lubrikant_Alkoholbasis)

Revision date: 06.06.2023 Product code: Page 8 of 12

Other information

No data available.

SECTION 12: Ecological information

12.1. Toxicity

The product has not been tested.

CAS No	Chemical name						
	Aquatic toxicity	Dose		[h] [d]	Species	Source	Method
64-17-5	ethanol; ethyl alcohol						
	Acute fish toxicity	LC50 mg/l	14200	96 h	Pimephales promelas	ECHA Dossier	
	Acute algae toxicity	ErC50	275 mg/l	72 h	Chlorella vulgaris	ECHA Dossier	
	Acute crustacea toxicity	EC50 mg/l	5012	48 h	Ceriodaphnia dubia	ECHA Dossier	
	Crustacea toxicity	NOEC	9,6 mg/l	9 d	Daphnia magna	ECHA Dossier	

12.2. Persistence and degradability

The product has not been tested.

CAS No	Chemical name				
	Method	Value	d	Source	
	Evaluation			•	
64-17-5	ethanol; ethyl alcohol				
	other guideline: -	84%	20	ECHA Dossier	
	Biodegradable.		•		

12.3. Bioaccumulative potential

No indication of bioaccumulation potential.

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
64-17-5	ethanol; ethyl alcohol	-0,35

12.4. Mobility in soil

No data available.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

The aforementioned statement applies to substances contained in the product with a minimum content of 0.1%.

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

The aforementioned statement applies to substances contained in the product with a minimum content of 0.1%.

12.7. Other adverse effects

No data available.

Further information

Do not allow to enter into surface water or drains.

SECTION 13: Disposal considerations

13.1. Waste treatment methods



according to Regulation (EC) No 1907/2006

coolTec II (Lubrikant_Alkoholbasis)

Revision date: 06.06.2023 Product code: Page 9 of 12

Disposal recommendations

Dispose of waste according to applicable legislation. Consult the local waste disposal expert about waste disposal. Non-contaminated packages may be recycled. According to (EWC) European Waste Catalogue, allocation of waste identity numbers/waste descriptions must be carried out in a specific way for every industry and process.

Control report for waste code/ waste marking according to (EWC) European Waste Catalogue:

List of Wastes Code - residues/unused products

160305 WASTES NOT OTHERWISE SPECIFIED IN THE LIST; off-specification batches and unused

products; organic wastes containing hazardous substances; hazardous waste

List of Wastes Code - used product

160305 WASTES NOT OTHERWISE SPECIFIED IN THE LIST; off-specification batches and unused

products; organic wastes containing hazardous substances; hazardous waste

List of Wastes Code - contaminated packaging

150110 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND

PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately collected municipal packaging waste); packaging containing residues of or contaminated by

hazardous substances; hazardous waste

Contaminated packaging

Handle contaminated packages in the same way as the substance itself.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number or ID number: UN 1170

14.2. UN proper shipping name: ETHANOL SOLUTION (ETHYL ALCOHOL SOLUTION)

14.3. Transport hazard class(es):314.4. Packing group:IIHazard label:3



Classification code: F1
Special Provisions: 144 601
Limited quantity: 1 L
Excepted quantity: E2
Transport category: 2
Hazard No: 33
Tunnel restriction code: D/E

Inland waterways transport (ADN)

14.1. UN number or ID number: UN 1170

14.2. UN proper shipping name: ETHANOL SOLUTION (ETHYL ALCOHOL SOLUTION)

14.3. Transport hazard class(es):314.4. Packing group:IIHazard label:3



Classification code: F1
Special Provisions: 144 601
Limited quantity: 1 L
Excepted quantity: E2



according to Regulation (EC) No 1907/2006

coolTec II (Lubrikant_Alkoholbasis)

Revision date: 06.06.2023 Product code: Page 10 of 12

Marine transport (IMDG)

14.1. UN number or ID number: UN 1170

14.2. UN proper shipping name: ETHANOL SOLUTION (ETHYL ALCOHOL SOLUTION)

14.3. Transport hazard class(es):314.4. Packing group:IIHazard label:3



Marine pollutant:

Special Provisions:

Limited quantity:

Excepted quantity:

Excepted quantity:

Excepted F-E. S-D

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number or ID number: UN 1170

14.2. UN proper shipping name: ETHANOL SOLUTION (ETHYL ALCOHOL SOLUTION)

14.3. Transport hazard class(es):314.4. Packing group:IIHazard label:3



Special Provisions: A3 A58 A180

Limited quantity Passenger: 1 L
Passenger LQ: Y341
Excepted quantity: E2

IATA-packing instructions - Passenger:353IATA-max. quantity - Passenger:5 LIATA-packing instructions - Cargo:364IATA-max. quantity - Cargo:60 L

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

14.6. Special precautions for user

See section 8.

14.7. Maritime transport in bulk according to IMO instruments

not relevant.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 40, Entry 75

2010/75/EU (VOC): not determined 2004/42/EC (VOC): not determined

Information according to 2012/18/EU P5c FLAMMABLE LIQUIDS

(SEVESO III):

Additional information

Safety Data Sheet according to Regulation (EC) No. 1907/2006 (amended by Regulation (EU) No 2020/878)

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].





according to Regulation (EC) No 1907/2006

coolTec II (Lubrikant_Alkoholbasis)

Revision date: 06.06.2023 Product code: Page 11 of 12

REACH 1907/2006 Appendix XVII, No (mixture): 3, 40

National regulatory information

Employment restrictions: Observe restrictions to employment for juveniles according to the 'juvenile

work protection guideline' (94/33/EC).

Water hazard class (D): 1 - slightly hazardous to water

15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information

Changes

Rev. 1,0; Initial release: 30.04.2018

Rev. 2,0; 04.01.2021, Changes in chapter: 5, 10, 16 Rev. 3,0; 06.06.2023, Changes in chapter: 1 - 16.

Abbreviations and acronyms

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement

concerning the International Carriage of Dangerous Goods by Road)

CAS: Chemical Abstracts Service

CLP: Classification, Labelling and Packaging of substances and mixtures

DNEL: Derived No Effect Level

d: day(s)

EINECS: European INventory of Existing Commercial chemical Substances

ELINCS: European LIst of Notified Chemical Substances

ECHA: European Chemicals Agency EWC: European Waste Catalogue

IARC: INTERNATIONAL AGENCY FOR RESEARCH ON CANCER

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)

ICAO: International Civil Aviation Organization

ICAO-TI: Technical Instructions by the "International Civil Aviation Organization" (ICAO)

GHS: Globally Harmonized System of Classification and Labelling of Chemicals GefStoffV: Gefahrstoffverordnung (Ordinance on Hazardous Substances, Germany)

h: hour

LOAEL: Lowest observed adverse effect level

LOAEC: Lowest observed adverse effect concentration

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

NOAEL: No observed adverse effect level

NOAEC: No observed adverse effect concentration

NLP: No-Longer Polymers N/A: not applicable

OECD: Organisation for Economic Co-operation and Development

PNEC: predicted no effect concentration PBT: Persistent bioaccumulative toxic

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de

fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

REACH: Registration, Evaluation, Authorisation of Chemicals

SVHC: substance of very high concern TRGS: Technische Regeln für Gefahrstoffe

UN: United Nations

VOC: Volatile Organic Compounds WGK: Water Hazard Class (Germany)





according to Regulation (EC) No 1907/2006

coolTec II (Lubrikant_Alkoholbasis)

Revision date: 06.06.2023 Product code: Page 12 of 12

Classification for mixtures and used evaluation method according to Regulation (EC) No 1272/2008 [CLP]

Classification	Classification procedure
Flam. Liq. 2; H225	On basis of test data

Relevant H and EUH statements (number and full text)

H225 Highly flammable liquid and vapour.

Further Information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)